

ELECTROPLATED THREADED ROD

- * **Materials** :- Mild Steel, Carbon Steel, Alloy Steel & Stainless Steel
- * **Standards** :- ASTM/ASME/DIN/BS EN ISO /JIS
- * **Threads** :- UNC, 8UN, UNF, Metric Coarse and Metric Fine
- * **Size Range** :- M6 to M100 in Metric series.
:- 1/4" to 4" in Imperial
:- Bigger sizes can be manufactured as per order.




* **Typical Grades & Standards** :-

- ASTM A193 Grade B7, B7M, B8, B8M & B16
- ASTM A320 Grade L7 & L7M
- BS 3692 / BS 4190 Grade 4.6, 4.8, 5.6, 5.8, 8.8
- Stainless Steel 304, 304L, 316, 316L, A2-70/80, A

* **Offering Information** :-

- Dimensions - Size.
- Standards and Grade
- Finish (Black, GI, Yellow, HDG, Cadmium, Nickel, PTFE etc)



Product Code	Threaded Rod Size (R)	Length (L) mm	Pitch (mm)	Minimum Proof Load (N)	Microns (μ)	Bundle Quantity
KLEPTR206	M6	2000	1	4.5	5 - 8	150
KLEPTR208	M8	2000	1.25	8.2	5 - 8	85
KLEPTR210	M10	2000	1.5	13.1	5 - 8	55
KLEPTR212	M12	2000	1.75	19	5 - 8	35
KLEPTR214	M14	2000	2	25.9	5 - 8	25
KLEPTR216	M16	2000	2	35.3	5 - 8	20
KLEPTR218	M18	2000	2.5	43.2	5 - 8	15
KLEPTR220	M20	2000	2.5	55.1	5 - 8	12
KLEPTR222	M22	2000	2.5	68.2	5 - 8	10
KLEPTR224	M24	2000	3	79.4	5 - 8	8
KLEPTR227	M27	2000	3	103	5 - 8	7
KLEPTR230	M30	2000	3.5	126	5 - 8	6
KLEPTR233	M33	2000	3.5	156	5 - 8	5
KLEPTR236	M36	2000	4	184	5 - 8	4
KLEPTR239	M39	2000	4	220	5 - 8	3
KLEPTR242	M42	2000	4.5	252	5 - 8	3
KLEPTR245	M45	2000	4.5	331	5 - 8	2
KLEPTR248	M48	2000	5	396	5 - 8	2
KLEPTR252	M52	2000	5	602	5 - 8	2

NOTE:-

- 1). OTHER DIMENSIONS AVAILABLE ON REQUEST.